Rain Streak

842 · J & 800 Series · Glass Film



842 Rain Streak Glass Film is part of our J & 800 Series Embossed Frosted Glass Film. Sandblast, floral and geometric embossed PVC — our core frosted range. Supplied in 1.23 m × 50 m rolls for export, by the container.

Applications

Offices & meeting rooms · Clinics & healthcare · Condominiums & homes

Specifications

Product code	**842**
Category	**Glass Film**
Series	**J & 800 Series**
Base material	**PVC**
Film thickness	**80 µm**
Finish	**Sandblast, floral and geometric embossing**
Adhesive	**Clear pressure-sensitive adhesive (PSA)**
Release liner	**80 g + 25 g PE-coated white release paper**
Roll width	**1.23 m**
Roll length	**50 m**

Installation summary

1. Clean the glass thoroughly; remove all dust, grease and residue.
2. Spray the glass and the adhesive side generously with slip solution (water with a few drops of baby shampoo).
3. Peel the liner, place the film, and squeegee from the centre outwards to remove water and air.
4. Trim the edges with a sharp blade, leaving a 1–2 mm gap from the frame.
5. Allow 7–14 days to cure fully; do not clean the film during this time.

The information in this data sheet is based on tests believed to be reliable and is given in good faith, but without warranty. Values are typical and may vary between production batches. Users should determine the suitability of the product for their own application, including compatibility with the glass and any glazing warranty. Specifications are subject to change without notice.