
Sandblast

CD-801 · CD Series · Cold Laminating Film



CD-801 Sandblast Cold Laminating Film is part of our CD Series Cold Laminating Film Effects. Textured and holographic overlaminates that protect and enhance prints and photos. Supplied in 0.635 m / 1.27 m / 1.524 m × 50 m rolls for export, by the container.

Specifications

Product code	**CD-801**
Category	**Cold Laminating Film**
Series	**CD Series**
Film thickness	**80 µm**
Adhesive	**Clear pressure-sensitive adhesive (PSA)**
Release liner	**120 g white kraft paper, single PE-coated**
Roll width	**0.635 m / 1.27 m / 1.524 m (25, 50 and 60 in)**
Roll length	**50 m (50 yd or 50 m, or to order)**
Other formats	**Also supplied in 3R, 4R and 5R sheets**

Installation summary

1. Ensure prints are fully dry or outgassed before laminating.
2. Laminate with a cold roll laminator at even tension and moderate roller pressure.
3. Allow 24 hours before trimming or mounting the laminated print.

The information in this data sheet is based on tests believed to be reliable and is given in good faith, but without warranty. Values are typical and may vary between production batches. Users should determine the suitability of the product for their own application, including compatibility with the glass and any glazing warranty. Specifications are subject to change without notice.