
Quatrefoil Lattice

PF-18-1 · PF Series · Glass Film



PF-18-1 Quatrefoil Lattice Glass Film is part of our PF Series Printed PET Glass Film. Linear stripes, grids and squares printed on 36 µm PET. Supplied in 1 m × 45 m rolls for export, by the container.

Applications

Offices & meeting rooms · Clinics & healthcare · Retail & shopfronts

Specifications

Product code	**PF-18-1**
Category	**Glass Film**
Series	**PF Series**
Base material	**PET**
Film thickness	**36 µm**
Finish	**Printed designs: stripes, rectangles, squares and more**
Adhesive	**Clear pressure-sensitive adhesive (PSA)**
Release liner	**25 µm single-coated transparent PET release liner**
Roll width	**1 m**
Roll length	**45 m**

Installation summary

1. Clean the glass thoroughly; remove all dust, grease and residue.
2. Spray the glass and the adhesive side generously with slip solution (water with a few drops of baby shampoo).
3. Peel the liner, place the film, and squeegee from the centre outwards to remove water and air.
4. Trim the edges with a sharp blade, leaving a 1–2 mm gap from the frame.
5. Allow 7–14 days to cure fully; do not clean the film during this time.

The information in this data sheet is based on tests believed to be reliable and is given in good faith, but without warranty. Values are typical and may vary between production batches. Users should determine the suitability of the product for their own application, including compatibility with the glass and any glazing warranty. Specifications are subject to change without notice.